



BEST AVAILABLE COPY



PCT/GB 2003 / 0 0 5 7 0 6




INVESTOR IN PEOPLE

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ




I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.


In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated 2 February 2004



10JAN03 E775863-2 002224
P01/7700 000-0300476.9

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1. Your reference
WBH
2. Patent application number
(The Patent Office will fill in this part)
0300476.9
3. Full name, address and postcode of the or of each applicant (underline all surnames)
AAAF-MCQUAY INC.
10300 Ormsby Park Place, Suite 600
Louisville, Kentucky 40223
U.S.A.
Patents ADP number (if you know it)
6969323002
If the applicant is a corporate body, give the country/state of its incorporation
U.S.A. - DELAWARE
ML 6/6/03 KR.
4. Title of the invention
VALVE
5. Name of your agent (if you have one)
JY & GW JOHNSON
"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)
Kingsbourne House
229-231 High Holborn
London
WC1V 7DP
Patents ADP number (if you know it)
8540742081
6. ☐ If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country	Priority application number (if you know it)	Date of filing (day / month / year)
---------	--	-------------------------------------
7. ☐ If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application	Date of filing (day / month / year)
-------------------------------	-------------------------------------
8. ☐ I am statement of inventorship and of right to grant of a patent required in support of this request? **Yes**

a. any applicant named in part 3 is not an inventor, or
b. there is an inventor who is not named as an applicant, or
c. any named applicant is a corporate body.
See note (d)

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form ☒ 2

Description 7

Claim(s) 2

Abstract

Drawing(s) 5 *15*

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*) 1

Request for substantive examination (*Patents Form 10/77*)

Any other documents
(*please specify*)

11. I/We request the grant of a patent on the basis of this application.

Signature

JY&GW Johnson

Date 9-1-03

12. Name and daytime telephone number of person to contact in the United Kingdom Mr W Hanson 020 74050356

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) *If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.*
- b) *Write your answers in capital letters using black ink or you may type them.*
- c) *If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- d) *If you have answered 'Yes' Patents Form 7/77 will need to be filed.*
- e) *Once you have filled in the form you must remember to sign and date it.*
- f) *For details of the fee and ways to pay please contact the Patent Office.*

VALVE

Background to the Invention

5 This invention relates to a valve, particularly, but not exclusively, for use in connection with a compressor.

10 Refrigeration and air-conditioning compressors often rely on the pressure difference generated by the compressor to provide the pressure difference needed to inject oil into the compressor for lubricating, sealing and cooling purposes. The pressure at the inlet (or "suction") of the compressor is dictated by the refrigeration duty being performed at the time. The delivery pressure at the outlet is dictated by the ability of the condenser of the refrigeration system to transfer heat to the condenser cooling medium. This medium may be ambient air or it may be a liquid such as water or a solution
15 containing an anti-freeze. The medium is in turn cooled by ambient air or a cooling tower.

20 At times, unless preventative action is taken, the pressure difference between delivery and suction can be too low to inject oil into the compressor. This can arise from either a high suction pressure, for example when the plant is started up after being turned off for a period, or it can arise from a low delivery pressure. The latter can again occur after the plant has been turned off for a period, or it can arise where the condenser cooling medium is at a very low temperature. Both high suction pressure and low delivery pressure
25 can be present at the same time. In some cases the condition would clear if the plant were allowed to continue running - but it cannot due to lack of oil injection. In other cases the cooling medium may be so cold that the condition would persist.

To remedy this situation it is necessary to fit means to keep the delivery pressure (as "seen" by the compressor and the oil system) high. One such means is a delivery/suction pressure control valve downstream of the compressor delivery and the oil separator/reservoir but upstream of the condenser. Such a valve is expensive.

Positive displacement compressors that do not have mechanical delivery valves (for example screw and scroll compressors) tend to act as expanders and rotate backwards when the driving force is switched off until the pressures in the evaporator and condenser equalise. This reverse migration of refrigerant from the high to the low-pressure side of the system is undesirable, as is the reverse rotation of the compressor, which can cause mechanical damage. To prevent this a non-return valve (also known as a check valve) is often fitted to the delivery line, downstream of the compressor delivery and the oil separator/reservoir but upstream of the condenser.

Summary of the Invention

It is an aim of the invention to provide a valve fulfilling the functions of both a delivery-to-suction pressure control valve and a non-return valve.

Accordingly, the invention provides a valve comprising a housing having an inlet and an outlet, and a pressure sensing port, a piston slidable in a part of the housing in response to a difference between a first fluid pressure at the pressure sensing port on the one side of the piston, and a second fluid pressure at the inlet and/or outlet on the other side of the piston, a valve member carried by the piston and operable thereby to close the inlet when said second fluid pressure is less than a value sufficiently greater than said first fluid pressure; wherein the valve member is movable with respect to the

piston to facilitate closing of the inlet, in response to a fluid flow from the housing to the inlet, when the piston is not acting to close the inlet.

Thus, the pressure difference sensing can fulfil the delivery-to-suction
5 pressure control function and the movement of the valve member with respect to the piston can provide the non-return function of the valve.

Piston biasing means may act to bias the piston into a position in which the valve member closes the inlet. This is one useful way of determining the
10 sufficiency of the difference between the first and second fluid pressures. The biasing means may comprise one or more helical springs.

The valve member can be formed with an inlet surface arranged to come into contact with a valve seat of the inlet and an opposed surface facing into the
15 housing. The valve member may have a stem slidably guided within a part of the piston. Valve member biasing means, such as a helical spring, may bias the valve member to close the inlet.

If the area of the opposed surface of the valve member is substantially equal
20 to the area of a surface of the piston facing said opposed surface, the forces applied to these surfaces by the fluid pressure will tend to be equal, such that only the force applied to the inlet surface of the valve member has to be considered.

25 In a particular embodiment of the invention, manual shut-off means are provided for closing the valve, for example for maintenance purposes. The manual shut-off means may comprise a spindle having a non-round proximal portion and a threaded distal portion. The distal portion may be engaged in a non-rotatable threaded sleeve, the sleeve being slidable along
30 the distal portion between a normal position in which the piston is movable

and a maintenance position in which the sleeve retains the piston and the valve member in the closed position. For example, in the maintenance position a distal end of the sleeve may abut a facing surface of the piston.

5 Brief Description of the Drawings

In order that the invention may be more readily understood, a particular embodiment thereof will now be described, by way of example only, with reference to the accompanying drawings, all showing a schematic section through a valve of the invention, and in which:

10

Figure 1 shows the valve in the maintenance condition;

Figure 2 shows the valve in a closed operative condition;

15 Figure 3 shows the valve in a partially-opened operative condition;

Figure 4 shows the valve in a fully-opened operative condition; and

Figure 5 shows the valve in a non-return condition.

20

Detailed Description of the Invention

The drawings show a valve comprising a housing 1 having an operating chamber 2 and a cylinder 3 communicating therewith. The operating chamber 2 has an inlet 4 and an outlet 5. A piston 6, slidable in the cylinder 3 with a close fit, extends into the operating chamber 2, and carries a valve member 7 which is arranged to close the inlet 4.

At the end of the cylinder shown at the top in the drawings, a port 8 is provided for sensing a fluid pressure. Where the invention is used in a

compressor arrangement, the port 8 may conveniently be connected to a suction side thereof.

5 A proximal end of the piston 6 has a generally cylindrical receptacle 9, in which two piston springs, such as helical compression springs, 10, 11 are mounted, one inside the other. The piston springs 10, 11 abut inner surfaces of the housing at one end and an opposing surface of the piston at the other end.

10 A distal end of the piston 6 is formed with a bore slidably receiving a stem 12 of the valve member 7. The valve member has a closing disk 13 attached to the stem 12 and arranged to close the inlet by means of an O-ring 14. A valve member spring 15 is mounted on the outside of the distal end of the piston, between the closing disk 13 and an opposed surface of the piston 6. In this
15 example, the valve member spring 15 is a helical compression spring exerting a significantly weaker force than either of the piston springs 10, 11.

Manual shut-off means, located at the proximal end of the piston 6, comprise a spindle 16 threadingly engaged with a slidable sleeve 17. The proximal
20 end 18 of the spindle 16 is non-round and extends from the housing. A peg 19, lodged in a part of the housing, extends into a longitudinal slot 20 in the sleeve.

The valve may, for example, have its inlet 4 connected to the delivery of a
25 compressor and its outlet 5 connected to the condenser of a refrigeration system.

Figure 1 shows the valve in the closed maintenance condition, after the proximal end 18 of the spindle has been turned, for example using a spanner.
30 Peg 19 prevents sleeve 17 from rotating, so that the engagement between the

thread of spindle 16 and that of sleeve 17 forces the latter to move downwardly to the position shown. The distal end of sleeve 17 abuts an opposing surface of piston 6, thusly holding the piston in its most advanced position, i.e. the bottom of its stroke as viewed. In this position, valve member 7 is fully closed and valve member spring 15 is compressed. No fluid can enter the inlet 4.

In figure 2, the valve is in the closed automatic or operative condition, spindle 16 having been fully turned, e.g. anticlockwise, to raise sleeve 17 and release piston 6. However, the pressure sensed at port 8 is too high and/or the pressure on the outer surface of closing disk 13 is too low. Piston springs 10, 11 are holding the piston 6 in its most advanced position so that valve member 7 closes inlet 4.

Figure 3 shows the valve in a partially-opened operative position. For example, the condenser pressure could be very low. There is enough pressure on the outer surface of closing disk 13, and on the distal surfaces of piston 6, to balance the pressure on the inner surface of closing disk 13, the pressure at port 8 (acting on the proximal surface of piston 6) and the force of piston springs 10, 11 which are more compressed than in Figure 2. Valve member 7 is open by a few millimetres and there is a flow of fluid, e.g. gas, through inlet 4, into chamber 2 and out of outlet 5. The apparent delivery pressure of the compressor is higher than the valve outlet (condenser) pressure, and the pressure difference between apparent delivery and suction is sufficient to inject enough oil into the compressor.

The valve has a modulating action, opening and closing to maintain a predetermined minimum pressure difference between apparent delivery and suction.

Figure 4 shows the valve in the fully-opened operative condition, in which the pressure difference is high across piston 6, the pressure in chamber 2 being significantly higher than the pressure at port 8. Springs 10, 11 are as compressed as possible. Fluid flows from inlet 4 to outlet 5 with only a small drop in pressure.

Figure 5 shows a condition in which fluid is tending to flow in reverse through the valve. For example, the compressor may have been switched off recently and there is still a large pressure difference across the piston 6 causing piston springs 10, 11 to remain compressed with the piston in its retracted position. "Weak" valve member spring 15, and the force of fluid in chamber 2 tending to flow towards closing disk 13, combine to extend valve member 7 from piston 6 and close inlet 4, thus preventing any reverse fluid flow.

It will therefore be seen that the invention has elegantly combined the functions of a pressure control valve and a non-return valve in a single unit. Additionally, the inventive valve can in certain embodiments also provide manual shut-off for maintenance purposes.

An additional benefit of combining the functions of the two or three valves previously necessary is that every valve causes a concomitant pressure drop. Thus, use of the valve of the invention significantly improves the total pressure drop between inlet and outlet.

CLAIMS

1. A valve comprising a housing having an inlet and an outlet, and a pressure sensing port, a piston slidable in a part of the housing in response to a difference between a first fluid pressure at the pressure sensing port on the one side of the piston, and a second fluid pressure at the inlet and/or outlet on the other side of the piston, a valve member carried by the piston and operable thereby to close the inlet when said second fluid pressure is less than a value sufficiently greater than said first fluid pressure; wherein the valve member is movable with respect to the piston to facilitate closing of the inlet, in response to a fluid flow from the housing to the inlet, when the piston is not acting to close the inlet.
2. A valve according to claim 1, wherein piston biasing means are arranged to bias the piston into a position in which the valve member closes the inlet.
3. A valve according to claim 2, wherein the piston biasing means comprise one or more helical springs.
4. A valve according to claim 1, 2 or 3, wherein the valve member is formed with an inlet surface arranged to come into contact with a valve seat of the inlet and an opposed surface facing into the housing.
5. A valve according to any preceding claim, wherein the area of the opposed surface of the valve member is substantially equal to the area of a surface of the piston facing said opposed surface.
6. A valve according to any preceding claim, wherein the valve member has a stem slidably guided within a part of the piston.

7. A valve according to any preceding claim, wherein valve member biasing means are arranged to bias the valve member to close the inlet.
8. A valve according to claim 7, wherein the valve member biasing means comprises a helical spring.
9. A valve according to any preceding claim, wherein manual shut-off means are provided for closing the valve.
10. 10. A valve according to claim 9, wherein the manual shut-off means comprise a spindle having a non-round proximal portion and a threaded distal portion.
11. A valve according to claim 10, wherein said distal portion is engaged in a non-rotatable threaded sleeve, the sleeve being slidable along the distal portion between a normal position in which the piston is movable and a maintenance position in which the sleeve retains the piston and the valve member in the closed position.
12. A valve substantially as described herein with reference to the accompanying drawings.




FIG 2




FIG 3

4/5




FIG 4

5/5





FIG 5

PCT Application
PCT/GB2003/005706



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.